



Powered by
INFRA.MARKET



SHALIMAR
PAINTS
SINCE 1902



HERO

WEATHER GUARD 12

SUPER LUXURY EXTERIOR EMULSION

Shalimar Hero Weather Guard 12 is a super luxury exterior paint formulated with advanced hybrid acrylic-PUD emulsion technology, specially designed for long-lasting wall protection. It delivers a rich, luxurious sheen finish with exceptional opacity, ensuring superior coverage and minimizing the need for multiple coats.

Engineered for performance, it comes with a 12-year durability warranty, offering long-term defense against environmental stresses. The formulation provides outstanding resistance to fading and includes heat-reflective properties, helping to reduce surface temperatures by up to 10°C, enhancing comfort and energy efficiency.

PRODUCT BENEFITS



**LUXURIOUS
SHEEN**



**WATER
REPELLENT**



**EXCELLENT
DPUR**



**HEAT PROTECTION
FORMULA**




**12-YEAR
DURABILITY**

PRODUCT FEATURES

WASHABILITY



**AVAILABLE
PACK SIZES**



**SHELF
LIFE**




FINISH



COVERAGE**



SHADES



VOC LEVEL

LOW VOC

APPLICATION PROCESS

Surface Preparation

- New surface must be cured for 28 days before painting and free from all water leakage related issues.
- Ensure the surface is clean, dry, and free from any loose particles, dust, grease, or oil. Growths of algae, fungus and moss should be removed by wire brushing and water followed by application of Bio block. Remove any older coatings using a scraper or wire brush. Ensure surface free from cracks and dents, suitable crack filler should be used.
- Sand the surface to ensure smoothness and better adhesion.

Primer

- Apply coat of Hero Interior Exterior Wall Primer by thinning with potable water (1:1 ratio by volume). Allow it to dry for 3-4 hrs. Spot prime before and after filling nail holes / cracks.

Putty (if required)

- Touch up application can be done with Shalimar Shakti Wall Guard putty followed, entire surface application by putty is not recommended.

Primer

- Stir Hero Interior Exterior Wall Primer thoroughly before use. Thin it 1:1 by volume with water and apply using a brush or roller. Allow it to dry for 3-4 hrs.

Top Coat

- Apply 2 coats by diluting 1 lit of Hero Weather guard 12 exterior emulsion with 300ml-400ml of water with the gap of 4-6hrs between two coats. Application can be done by brush or roller. For dark shades, requires additional coats for better hiding and appearance.

Application Surfaces

- All kinds of well-prepared plaster, concrete, and masonry surfaces.

**Coverage - Actual coverage may vary as coverage depends on method and condition of application as well as surface roughness and porosity.

PRECAUTIONS



- Do not apply when the ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs of application.
- Do not apply when humidity is greater than 90%. It may cause prolonged drying time of paint and moisture condensation on the walls.
- Do not over-thin or over-extend the brush.
- Tint using Shalimar Paints machine colorants only.
- Stir well and strain before use.
- Tinted paints need thorough shaking immediately after tinter addition as well as before use.
- For best performance, ensure that the surface is dry. On moisture meter, the reading should be below 16%. In case it is above that, find out the source of water and address it before painting.
- For better washability ensure the paint surface is cured for 2 weeks under normal atmospheric conditions (30°C; 50 - 60%RH).
- For extremely rough surface including textures: Application by brush is recommended to ensure all the grooves are covered well.

SAFETY FEATURES



- As a general safety measure, inhalation of paint mist and contact of liquid paint with skin & eyes should be avoided.
- Forced ventilation should be provided when applying paint in confined spaces or stagnant air.
- Even when ventilation is provided, respiratory, skin and eye protection are always recommended when spraying paint.
- Store the container with the lid tightly closed in an upright position, in a cool, dry place
- Keep out of reach of children and away from eatables.
- May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not breathe vapors or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- Left-Over Paint Disposal: Left-over paint/drums should not be disposed in soil/drains. Consumers should consult a local recycling agency for proper disposal of paint/drums.
- In the event of spills, contain spillage using sand or earth.
- No added Lead, Mercury or Chromium compounds.

For Feedback/Complaints write at feedback@shalimarpaints.com

Registered Corporate Address Shalimar Paints, Stainless Centre, 4th Floor, Plot No. 50, Sector - 32, Gurugram, 122001, Haryana
Tel.: 0124-4616600, Toll Free : 1800-103-6509

DISCLAIMER

[*Spreading Capacity may vary depending upon the surface condition, porosity of the surface and method of application]

This PDS is by no means a comprehensive data. The company will not be liable for losses or damages howsoever caused including liability for negligence, which may be suffered by the user of the data contained therein. It is the user's responsibility to conduct all necessary tests to confirm the suitability of any product or system for their intended use. No guarantee of result is extended since conditions of use are beyond our control.