

PRODUCT NAME:
NO.1 PREMIUM ACRYLIC DISTEMPER



NO.1 PREMIUM ACRYLIC DISTEMPER

It is a water-based interior acrylic wall distemper with better opacity and high coverage offering rich matt finish. Its non-chalking features give bright and clean shades resulting into beautiful walls

PRODUCT BENEFITS



EASE OF APPLICATION



VALUE FOR MONEY



SMOOTH FINISH



HIGH COVERAGE



EXCELLENT WHITENESS

PRODUCT FEATURES

AVAILABLE
PACK SIZES



SHELF
LIFE



COLORS
AVAILABLE



FINISH



COVERAGE



APPLICATION DETAILS

Surface Preparation

- New surface to be cured 28 days before painting and free from all waterproofing issues.
- Prepare the surface by using suitable sand/emery paper or scrapping tools to remove dirt, dust, grease, loose flaking paint, laitance, algae, fungi etc. and wipe it clean.

a) Primer

- Apply coat of Shalimar Water Thinnable Cement Primer as per recommendation. Allow it to dry for 3-4 Hrs or apply coat of Shalimar Universal White Primer as per recommendation. Allow it to dry 6-8 hrs.
- Spot prime before and after filling nail holes / cracks.

b) Putty (if required)

- Level the surface with Shalimar Magic Acrylic Wall Putty or Shalimar Shakti Wall Guard putty and allow it to dry for 4-6 hrs.
- Sand surface with 180/320 emery paper and wipe it clean.
- Apply an additional coat depending upon the surface conditions and smoothen the surface.

c) Top Coat

- Thin No.1 Premium Acrylic Distemper with potable water, 50% to 60% by weight.
- Apply 2 coats of Distemper with an interval of 4-6 hrs. Application can be done by brush, roller or spray.
- For dark shades require additional coats for better hiding and appearance.

d) Application Surfaces

- All kind of well-prepared interior plasters, concrete and masonry surfaces.

NO. 1 PREMIUM ACRYLIC DISTEMPER

PRECAUTIONS



- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs of application.
- Do not apply when humidity is greater than 90%. It may cause prolonged drying time of paint and moisture condensation on the walls.
- Do not over-thin or over-extend the brush.
- Tint using Shalimar Paints machine colorants only.
- Stir well and strain before use.
- Tinted shades need thorough shaking immediately after colourants addition as well as before use.
- For best performance, ensure that the surface is dry. On moisture meter, the reading should be below 16%. In case it is above that, find out the source of water and address it before painting.

SAFETY FEATURES



- Kindly refer to the MSDS for detailed information on safety measures while handling the paint, which is available on request.
- Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- Keep out of reach of children and away from eatables.
- May be harmful, if swallowed. In case of ingestion seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not breathe vapour or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- Left-Over Material Disposal: Left-over material/drums should not be disposed in soil/drains. Consumers should consult a local recycling agency for proper disposal of paint/drum.
- In the event of spills, contain spillage using sand or earth.
- No added Lead, Mercury or Chromium compounds.

For Feedback/Complaints write at feedback@shalimarpaints.com
Registered Corporate Address Shalimar Paints, Stainless Centre, 4th Floor, Plot No. 50, Sector - 32, Gurugram, 122001, Haryana
Tel.: 0124-4616600, Toll Free : 1800-103-6509

DISCLAIMER

(*Spreading Capacity may vary depending upon the surface condition, porosity of the surface and method of application)

This PDS is by no means a comprehensive data. The company will not be liable for losses or damages howsoever caused including liability for negligence, which may be suffered by the user of the data contained therein. It is the user's responsibility to conduct all necessary tests to confirm the suitability of any product or system for their intended use. No guarantee of result is extended since conditions of use are beyond our control.