



SHALIMAR
PAINTS
SINCE 1902



SMART BHARAT

INTERIOR & EXTERIOR PAINT

SMART BHARAT is water-based acrylic paint which makes it ideal for both interior and exterior surfaces. It is affordable economical paint that can be used to paint beautiful building at the cost of Distemper. It provides best in class biopack for fungal /algal resistance, film strength better than local Distempers /cement paints.

PRODUCT BENEFITS



BUDGET FRIENDLY
2 IN 1 PAINT



WARRANTY*



**BETTER
DURABILITY**



VIBRANT SHADES



**ECO-FRIENDLY
& SAFE**

PRODUCT FEATURES

Colour	White
Finish	Smooth and Matt
Method of Application	Brush/Roller
No. of Coats recommended	Dilute 1 Kg paint with up to 400 -500 ML water depending upon the consistency & application surface
Drying time @30 ° C & RH <=65 %	
Theoretical Spreading Rate	35-45-Sq. ft. / Kg. (Ext Application) 90-110-Sq. ft./ Kg. (Int. Application) <small>*Spreading rate depends on film thickness applied, type of texture surface porosity, surface preparation, wastage during painting, etc.</small>
Volatile Organic Compound	Low Voc
Flash Point	Non-flammable since it is water based product.
Storage life	3 years from date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

AVAILABLE
PACK SIZES



5 kg



10 kg



20 kg

APPLICATION PROCESS

Surface Preparation

- New surface must be cured for 28 days before painting and free from all water leakage related issues. Ensure the surface is clean, dry, and free from any loose particles, dust, grease, or oil. Remove any older coatings using a scraper or wire brush. Ensure surface free from Cracks and dents, suitable crack filler should be used. Sand the surface to ensure smoothness and better adhesion.

Primer

- Apply coat of Shalimar Interior Exterior acrylic Wall Primer by thinning with potable water (1:1 ratio by volume). Allow it to dry for 3-4 hrs. Spot prime before and after filling nail holes / cracks.

Putty

- For Interior surfaces: Level the surface with Shalimar Shakti Wall Guard putty and allow it to dry for 4-6 hrs. Sand surface with 180/320 emery paper and wipe it clean.
- For Exterior surfaces: Touch up application can be done with Shalimar Shakti Wall Guard putty followed by primer application, entire surface application by putty is not recommended.

Top Coat

- Apply 2-3 coats of Smart Bharat interior exterior paint by diluting it with potable water (35-45% by weight) with the gap of 4-6 hrs between two coats. Application can be done by brush or roller. For dark shades, requires additional coats for better hiding and appearance.



SHALIMAR
PAINTS
SINCE 1902

SMART BHARAT INTERIOR & EXTERIOR PAINT

PRECAUTIONS



- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs. of application.
- Do not apply when humidity is greater than 90%.
- Tint using Shalimar Paints machine colorants only, once tinted, do thorough shaking immediately as well as before use, Stir well and strain before use.
- For extremely rough surface including textures: Application by brush is recommended to ensure all the grooves are covered well

***Refer warranty documents**

For Feedback/Complaints write at feedback@shalimarpaints.com
Registered Corporate Address Shalimar Paints, Stainless Centre, 4th Floor, Plot No, 50, Sector - 32, Gurugram, 122001, Haryana
Tel.: 0124-4616600, Toll Free : 1800-103-6509

DISCLAIMER

(*Spreading Capacity may vary depending upon the surface condition, porosity of the surface and method of application)

This PDS is by no means a comprehensive data. The company will not be liable for losses or damages howsoever caused including liability for negligence, which may be suffered by the user of the data contained therein. It is the user's responsibility to conduct all necessary tests to confirm the suitability of any product or system for their intended use. No guarantee of result is extended since conditions of use are beyond our control.