SHALIMAR PAINTS
SINCE 1902



SMART BHARAT VASTU

INTERIOR & EXTERIOR EMULSION

SMART BHARAT VASTU is a unique multipurpose and durable water-based acrylic emulsion which makes it ideal for both interior and exterior surfaces. It is the best-in-class economical Interior and Exterior emulsion that can create beautiful walls in the cost of Distemper. It provides best-in-class bio pack for fungal /algal resistance, with film strength better than any Distempers or cement paint. Special Features of Smart Bharat Vastu are designed to promote a positive ambience through negative ion, with fragrance incorporation, and specially curated Vastu-inspired shades for a refreshing and harmonious living environment.

PRODUCT BENEFITS

- 2 IN 1 EMULSION — BUDGET FRIENDLY 2 IN 1 EMULSION
- POSITIVE ENERGY PROJECTION
- SPECIAL VASTU SHADES
- SANDALWOOD FRAGRANCE
- 2 YEARS WARRANTY — 2 YEARS WARRANTY

PRODUCT FEATURES

Colour	White
Finish	Smooth and Matt
Method of Application	Brush/Roller
No. of Coats recommended	2 Coat
No. of Coats recommended	Dilute 1 Kg paint with up to 300-400 ML water depending upon the consistency and application surface.
Drying time @30 ° C & RH </=6 %	
Theoretical Spreading Rate	35-45-Sq. ft. / Kg. (Ext Application) 90-110-Sq. ft./ Kg. (Int. Application) *Spreading rate depends on film thickness applied, type of texture surface porosity, surface preparation, wastage during painting, etc.
Volatile Organic Compound	Low Voc
Flash Point	Non-flammable since it is water based product.
Storage life	5 years from date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

AVAILABLE PACK SIZES



APPLICATION PROCESS

Surface Preparation
New surface must be cured for 28 days before painting and free from all water leakage related issues. Ensure the surface is clean, dry, and free from any loose particles, dust, grease, or oil. Remove any older coatings using a scraper or wire brush. Ensure surface free from Cracks and dents, suitable crack filler should be used. Sand the surface to ensure smoothness and better adhesion.

Primer
- Apply coat of Shalimar Interior Exterior acrylic Wall Primer by thinning with potable water (1:1 ratio by volume).
- Allow it to dry for 3-4 hrs. Spot prime before and after filling nail holes / cracks.

Putty (if required)
- For Interior surfaces: Level the surface with Shalimar Shakti Wall Guard putty and allow it to dry for 4-6 hrs. Sand surface with 180/320 emery paper and wipe it clean.
- For Exterior surfaces: Touch up application can be done with Shalimar Shakti Wall Guard putty followed by primer application, entire surface application by putty is not recommended.

Primer
- Apply coat of Shalimar Interior Exterior acrylic Wall Primer by thinning with potable water (1:1 ratio by volume). Allow it to dry for 3-4 hrs.

Top Coat
- Apply 2-3 coats of Smart Bharat interior exterior paint by diluting it with potable water (35-45% by weight) with the gap of 4-6 hrs between two coats. Application can be done by brush or roller. For dark shades, requires additional coats for better hiding and appearance.

Application Surfaces
All kinds of Interior and exterior plaster, concrete and masonry surfaces.

SMART BHARAT VASTU INTERIOR & EXTERIOR EMULSION

PRECAUTIONS



- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs. of application.
- Do not apply when humidity is greater than 90%.
- Tint using Shalimar Paints machine colorants only, once tinted, do thorough shaking immediately as well as before use, Stir well and strain before use.
- For extremely rough surface including textures: Application by brush is recommended to ensure all the grooves are covered well

*Refer warranty documents

Website: www.shalimarpaints.com | Feedback/Complaints: feedback@shalimarpaints.com
Registered Office: Shalimar Paints Ltd, Stainless Centre, 4th floor, plot no. 50. Sector 32, Gurugram, Haryana - 122001
Corporate Office: Olethia Business Spaces, Road No 16Z, Opp. Ashar IT Park, Wagle Industrial Estate, Thane (W) 400604
Tel.: 0124-4616600, **Toll Free:** 1800 103 6509

DISCLAIMER

(*Spreading Capacity may vary depending upon the surface condition, porosity of the surface and method of application)

This PDS is by no means a comprehensive data. The company will not be liable for losses or damages howsoever caused including liability for negligence, which may be suffered by the user of the data contained therein. It is the user's responsibility to conduct all necessary tests to confirm the suitability of any product or system for their intended use. No guarantee of result is extended since conditions of use are beyond our control.

Powered by INFRA.MARKET