



**SHALIMAR
PAINTS**
SINCE 1902

INTRODUCING **PU GLOSS & SATIN ENAMEL**



TIMELESS PREMIUM FINISH FOR METAL & WOOD



Powered by **INFRA.MARKET**

SUPERLAC ENAMEL PU GLOSS SHADES



Golden Brown*



PO Red*



Phirozi*



Smoke Grey*



Golden Yellow*



Brown**

* Available shades for PU Gloss

** Available shades for PU Gloss and PU Satin

• PU Gloss and PU Satin are also available in White and Black shades
Shade chip show approximate paint shade only. Actual shade may vary.

SUPERLAC ENAMEL PU GLOSS



**SUPER GLOSSY
FINISH**



**2 YEARS
WARRANTY**



**FAST
DRYING**



**TOUGH &
DURABLE**

SUPERLAC ENAMEL PU SATIN



**2 YEARS
WARRANTY**



**STAIN RESISTANT
FORMULA**



**TOUGH & DURABLE
SOFT SHEEN FINISH**



**EXCELLENT
WASHABILITY**



DIRECTIONS FOR USE

Applicable for: **PU Gloss & PU Satin**

Surface Preparation:

Sand the surface with 180 emery paper to remove dirt, oil, grease, and loose flaking particles of old paint. Wipe it clean.

Fill dents and imperfections using an appropriate filler.

Priming:

Apply a suitable coat of primer depending on the surface, using the recommended dilution mentioned on the pack

- Ferrous Metal Surface: Shalimar Red Oxide Metal Primer
- Wood Surface: Shalimar Pink Primer / Universal White Primer
- Masonry Surface: Shalimar Universal White Primer

Allow 6–8 hours drying time for the primer coat. Lightly sand with emery paper 320, and wipe clean. Apply an additional coat of primer if required.

Top Coat Application:

Stir the paint thoroughly and strain it through a muslin cloth before use.

Product	Brush Application	Spray Application
PU Satin	10–15% Shalimar MTO / GP thinner	Up to 20% Shalimar MTO / GP thinner
PU Gloss	5–7% Shalimar MTO	Up to 15% Shalimar MTO

Avoid over or under dilution as it affects finish and performance. Apply 2–3 coats of the respective product over the primed surface.

Maintain a gap of:

- PU Satin: 8–10 hours between coats
- PU Gloss: 6–8 hours between coats

If needed, do light sanding with emery paper 400 between coats for a smooth finish. Drying time may vary with ambient temperature and humidity. Ensure the surface is fully dry before recoating.

Precautions:

- Do not apply if ambient temperature is below 10°C or if it may drop within 4–6 hours of application.
- Avoid application in wet weather or on moist surfaces.
- Do not over-thin the paint.
- Stir well before use.

Recommended Surfaces: Both PU Gloss and PU Satin are suitable for

- Wood
- Metal
- Masonry surfaces



SHALIMAR
PAINTS
SINCE 1902

Regd. Office: Stainless Centre, 4th Floor, Plot No. 50, Sector - 32, Gurugram, 122001, Haryana.

Corporate Office: Shalimar Paints Limited, Olethia Business Spaces, Road No 16Z, Opp. Ashar IT Park, Wagle Industrial Estate, Thane (W), Maharashtra - 400604.