

PRODUCT NAME:
SUPERLAC ENAMEL PU SATIN



SUPERLAC ENAMEL PU SATIN

Superlac PU Satin Enamel is a PU reinforced enamel which imparts robust and tough paint film providing superior durability. Contributing to cleaner and more hygienic surfaces, it resists bacterial & fungal attack, keeping the paint looking as good as new for a long time. With 2 years warranty, choose Superlac PU Satin Enamel when you demand the best in quality and performance.

PRODUCT BENEFITS



FUNGAL
RESISTANCE



EXCELLENT
WASHABILITY



STAIN RESISTANT
FORMULA



TOUGH & DURABLE
SOFT SHEEN FINISH



2 YEARS
WARRANTY

PRODUCT FEATURES

AVAILABLE
PACK SIZES



SHELF
LIFE



COLORS
AVAILABLE



FINISH



COVERAGE



APPLICATION DETAILS

Surface Preparation

- Sand surface with 180 emery paper to remove dirt, oil, grease and loose flaking particles of old paint etc. Wipe it clean.

Priming

- Apply a coat of primer depending upon the surface as per recommended dilution mentioned on pack. For Ferrous Metal Surface – Shalimar Red Oxide Metal Primer, for Nonferrous Surfaces – Shalimar ETCH Primer, for Wood Surface – Shalimar Pink Primer / Universal White Primer, for Masonry Surfaces – Shalimar Universal White Primer. Ensure drying time of at least 6-8 hours for primer coat.
- Sand the surface lightly with emery paper 320 and wipe it clean. Apply an additional coat of appropriate primer (if required).

Top coat application

- Stir the paint thoroughly and strain through a muslin cloth before use. Dilute Shalimar PU satin with 10-15% of MTO/ GP thinner for brush application and up to 20% in case of spray application. Over dilution will affect the finish and performance of the product. Stir the paint thoroughly after dilution and apply 2-3 coats of Shalimar PU Satin over the primer coat. Intervals between each coat is 8-10 hours. If required do light sanding with emery paper 400 between the coats for proper finishing. Drying time may vary according to the temperature and humidity of external environment and hence be cautious of the same and check thoroughly before recoating.

Precaution

- Do not apply if the ambient temperature is less than 10°C or in case there is a possibility of temperature drop to this level within 4- 6 hours. Do not apply it in wet weather or in case there is moisture on surface. Do not over thin the paint. Stir well before use.

Application surfaces

- Wood, Metal and Masonry Surfaces.

PRECAUTIONS



- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs of application.
- Do not apply when humidity is greater than 90%. It may cause prolonged drying time of paint and moisture condensation on the walls.
- Do not over-thin or over-extend the brush.
- Tint using Shalimar Paints machine colorants only.
- Stir well and strain before use.
- Tinted shades need thorough shaking immediately after colourants addition as well as before use.
- For best performance, ensure that the surface is dry. On moisture meter, the reading should be below 16%. In case it is above that, find out the source of water and address it before painting.

SAFETY FEATURES



- Kindly refer to the MSDS for detailed information on safety measures while handling the paint, which is available on request.
- Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- Keep out of reach of children and away from eatables.
- May be harmful, if swallowed. In case of ingestion seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not breathe vapour or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- Left-Over Material Disposal: Left-over material/drums should not be disposed in soil/drains. Consumers should consult a local recycling agency for proper disposal of paint/drum.
- In the event of spills, contain spillage using sand or earth.
- No added Lead, Mercury or Chromium compounds.

Website: www.shalimarpaints.com | Feedback/Complaints: feedback@shalimarpaints.com
Registered Office: Shalimar Paints Ltd, Stainless Centre, 4th floor, plot no. 50. Sector 32, Gurugram, Haryana - 122001
Corporate Office: Olethia Business Spaces, Road No 16Z, Opp. Ashar IT Park, Wagle Industrial Estate, Thane (W) 400604
Tel.: 0124-4616600, Toll Free: 1800 103 6509

DISCLAIMER

(*Spreading Capacity may vary depending upon the surface condition, porosity of the surface and method of application)

This PDS is by no means a comprehensive data. The company will not be liable for losses or damages howsoever caused including liability for negligence, which may be suffered by the user of the data contained therein. It is the user's responsibility to conduct all necessary tests to confirm the suitability of any product or system for their intended use. No guarantee of result is extended since conditions of use are beyond our control.