SHALIMAR PAINTS
SINCE 1902



SUPERLAC STAY CLEAN

SUPER PREMIUM WASHABLE INTERIOR EMULSION

Superlac Stay Clean is a premium water-based emulsion powered by advanced Hydroclean Technology. It offers superior resistance to everyday household stains such as tea, coffee, ketchup, and more. With high scrub cycles and an 8-year warranty, it keep walls clean, shiny, and fresh for longer.

PRODUCT BENEFITS

- EASY CLEANABILITY
- 1800+ SCRUB CYCLES
- SUPERIOR STAIN RESISTANCE
- LOW VOC 30-40 GRAMS/LITRE
- HIGH SHEEN
- 8 YEARS WARRANTY

PRODUCT FEATURES

WASHABILITY	LOW · MEDIUM · HIGH · EXCELLENT
AVAILABLE PACK SIZES	1 ltr · 4 ltr · 10 ltr · 20 ltr
SHELF LIFE	3 Years FROM THE DATE OF MANUFACTURING
COLORS AVAILABLE	2000+ SHADES
FINISH	SHEEN · SOFT SHEEN · HIGH SHEEN ✓ · SMOOTH ✓
COVERAGE	120–130 Sq Foot/Liter/2 coat.

APPLICATION DETAILS

Surface Preparation

- Prepare the surface by using suitable sand/emery paper or scraping tools to remove dirt, dust, grease, loose flaking paint, laitance, algae, fungi etc. and wipe it clean

Primer

- Apply a coat of Hero Interior Exterior Primer (or any other suitable Shalimar Paints primer) as per recommendation. Allow it to dry for 3-4 hours
- Spot prime before and after filling nail holes/cracks

Putty (if required)

- Level the surface with Shalimar Magic Acrylic Wall Putty or Shalimar Shakti Wall
- Guard Putty and allow it to dry for 4-6 hours
- Sand the surface with 180/320 emery paper and wipe it clean
- Apply an additional coat depending upon the surface conditions and smoothen the surface

Primer

- Apply a coat of Hero Interior Exterior Primer (or any other suitable Shalimar Paints primer) as per recommendation. Allow it to dry for 3-4 hours. In case application is done with Shalimar Universal White Primer allow it to dry for 6-8 hours

Top Coat

- Thin Superlac Stay Clean with potable water, 40% to 50% by volume
- For dark shade, thin Superlac Stay Clean with potable water 25%-30% by volume
- Apply 2 coats of Superlac Stay Clean Emulsion with an interval of 4-6 hours
- Application can be done by brush, roller or spray
- For dark shades, an additional coat is recommended

Application Surfaces

- All kinds of well-prepared plaster, concrete and masonry surfaces.

SUPERLAC STAY CLEAN

SUPER PREMIUM WASHABLE INTERIOR EMULSION

SHALIMAR PAINTS SINCE 1902

PRECAUTIONS



- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs of application.
- Do not apply when humidity is greater than 90%. It may cause prolonged drying time of paint and moisture condensation on the walls.
- Do not over-thin or over-extend the brush.
- Tint using Shalimar Paints machine colorants only.
- Stir well and strain before use.
- Tinted shades need thorough shaking immediately after colourants addition as well as before use.
- For best performance, ensure that the surface is dry. On moisture meter, the reading should be below 16%. In case it is above that, find out the source of water and address it before painting.
- For better washability ensure the paint surface is cured for 2 weeks under normal atmospheric conditions (30°C ; 50 - 60%RH].
- Application of Acrylic Wall Putty and adherence to the painting system is mandatory for best results.

SAFETY FEATURES



- Kindly refer to the MSDS for detailed information on safety measures while handling the paint, which is available on request.
- Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- Keep out of reach of children and away from eatables.
- May be harmful, if swallowed. In case of ingestion seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not breathe vapour or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- Left-Over Material Disposal: Left-over material/drums should not be disposed in soil/drains. Consumers should consult a local recycling agency for proper disposal of paint/drum.
- In the event of spills, contain spillage using sand or earth.
- No added Lead, Mercury or Chromium compounds.

For Feedback/Complaints write at feedback@shalimarpaints.com
Registered Corporate Address Shalimar Paints, Stainless Centre, 4th Floor, Plot No. 50, Sector - 32,Gurugram, 122001, Haryana
Tel.:0124-4616600, Toll Free : 1800-103-6509

DISCLAIMER

(*Spreading Capacity may vary depending upon the surface condition, porosity of the surface and method of application)

This PDS is by no means a comprehensive data. The company will not be liable for losses or damages howsoever caused including liability for negligence, which may be suffered by the user of the data contained therein. It is the user's responsibility to conduct all necessary tests to confirm the suitability of any product or system for their intended use. No guarantee of result is extended since conditions of use are beyond our control.