

# SHAKTI CEMENT PUTTY

Shakti cement putty is cement base putty, it gives good adhesion, prevent flacking, excellent smoothness and good whiteness. It increases the coverage as well as life of top coat.

## PRODUCT BENEFITS



**ZERO  
VOC**

The eco-friendly product contains minimum harmful elements to protect your families better



**EXCELLENT  
ADHESION**

The enhanced acrylic emulsion formulation results in better durability of the top coat



**ANTI  
FLACKING**

Special additives and fine pigments imparts the rich finish with anti-flacking properties



**EASE OF  
APPLICATION**

The easy to apply feature helps to color your wall in the most hassle free way



**EASILY  
COMPATIBLE**

Easy to apply any kind of water base paint on it

## PRODUCT FEATURES

AVAILABLE  
PACK SIZES



SHELF  
LIFE



**1 Year**  
FROM THE DATE OF MANUFACTURING

FINISH



SMOOTH

COVERAGE



**9-15**  
SQ. FEET/LIT COAT

## APPLICATION PROCESS

Ensure that surface is free from dirt, loss particles etc. Mix Shakti putty with portable water in slowly way. Ensure that proper (homogenous) paste is form. This paste is ready for application. Please note that paste will be no longer than 3-4 hrs. it will be hard. Accordingly, freshly make every times.

## PRECAUTIONS



- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs of application.
- Do not apply when humidity is greater than 90%. It may cause prolonged drying time of paint and moisture condensation on the walls.
- Do not over-thin or over-extend the brush.
- Tint using Shalimar Paints machine colourants only
- Stir well and strain before use.
- Tinted paints need thorough shaking immediately after tinter addition as well as before use. For best performance, ensure that the surface is dry.
- On moisture meter, the reading should be below 16%. In case it is above that, find out the source of water and address it before painting.
- For better washability ensure the paint surface is cured for 2 weeks under normal atmospheric conditions. (30°C ; 50 - 60 %RH)
- Application of Acrylic Wall Putty and adherence to the painting system is mandatory for best results.

## SAFETY FEATURES



- Kindly refer to the MSDS for detailed information on safety measures while handling the paint, which is available on request.
- Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- Keep out of reach of children and away from eatables.
- May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not breathe vapour or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation
- Left-Over Paint Disposal: Left-over paint/drums should not be disposed in soil / drains. Consumers should consult a local recycling agency for proper disposal of paint/drums.

For Feedback/Complaints write at [feedback@shalimarpaints.com](mailto:feedback@shalimarpaints.com)

**Registered Corporate Address** Shalimar paints Stainless Centre, 4th Floor, Plot No. 50, Sector - 32, Gurugram, 122001, Haryana  
Tel.: 0124-4616600, Fax.: 0124-4616659, Toll Free : 1800-103-6509

### DISCLAIMER

[\*\*Spreading Capacity may vary depending upon the surface condition, porosity of the surface and method of application]

This PDS is by no means a comprehensive data. The company will not be liable for losses or damages howsoever caused including liability for negligence, which may be suffered by the user of the data contained therein. It is the user's responsibility to conduct all necessary tests to confirm the suitability of any product or system for their intended use. No guarantee of result is extended since conditions of use are beyond our control.