

CANKOTE

PACKAGING ~ METAL DECORATION COATING

Q.D. SIDE STRIP COATING Data Sheet No. SPL/PMG/519017_200387001017

- Lead and chrome free modified resin based one pack air drying side strip external coating.
- Excellent abrasion and mar resistance

Exhibits excellent dust free properties

🔀 feedback@shalimarpaints.com

 Excellent adhesion and chemical resistance properties

	Product Information	Application details
Chemistry	Modified resin based	Method of Application
Colour	Clear	Brush/Cotton wool /Spray
Supply Viscosity FCB4 @ 30 °C	20 ± 3 Seconds	Thinner Epoxy reducer
Mixing Ratio (By Volume)	Single pack	It is always recommended to Stir material before use
Solid content by mass	25 ± 2 %	Intended Use
Dry film by weight	3-4 mgm/ linear Square inch	This is an excellent for external coating for pesticide and non food grade liquids and solids
Specific Gravity	0.87 ± 0.02	
Scotch tape adhesion 1mm as per ASTM 3359	5B (Excellent)	Substrate - Tin, Tin free steel(TFS), Electrolytic Tinplate (ETP)
Flash Points	Above 25 °C	For more details contact Representative of Shalimar Paints Limited
Storage Life	Up to 6 months when stored in sealed containers 30±5 °C	Pack Size 20 litres

Health & Safety

Use Proper Personal Protective Equipment(PPE) during application of this product. Please consult Material Safety Datasheet (MSDS)

Precaution

Provide adequate ventilation during application and drying. Clean Spray gun equipment and hose immediately after application of material.

This product datasheet supersedes all previous datasheet Q.D. Side Strip Coaing 51/90/17-87001017 Abbreviation used - EMT – Effective Metal temperature ; mgm – Milligram, FCB4 – Ford cup b4

> h Floor, Plot No. 50, Rhone 1800-103-6509

DISCLAIMER: This PDS is by no means a comprehensive data. The company will not be liable for losses or damages howsoever caused including liability for negligence, which may be suffered by the user of the data contained therein. It is the user's responsibility to conduct all necessary tests to confirm the suitability of any product or system for their intended use. No guarantee of result is extended since conditions of use are beyond our control. Liability is limited to replacement of the product hence cost of labour charges or consequential damages are excluded.

Revision 3/0420